



## SERVIZIO Namor® 1

Product number: 5025013

Configuration: stainless steel, without laminar aerator, low pressure

### Configuration options

- 5025001 | stainless steel, with laminar aerator, high pressure
- 5025002 | black matt, with laminar aerator, high pressure
- 5025013 | stainless steel, without laminar aerator, low pressure
- 5025014 | black matt, without laminar aerator, low pressure

- ✓ Sink faucet
- ✓ low pressure
- ✓ with swivelling outlet

Single lever faucet. With swivelling outlet and ceramic cartridge.

— swivel range 120°

— drill Ø 35 mm

— corresponds to the German and European drinking water regulation/directive



[more infos...](#)

### Technical data

|                                      |                        |                             |  |
|--------------------------------------|------------------------|-----------------------------|--|
| Article type                         | Sink faucet            | Swivel range outlet         | 120°   |
| Brand                                | SERVIZIO               | Beam type                   | Laminar beam   |
| Number of handles                    | 1                      | Operating pressure          | low pressure   |
| Total installation height            | 273 mm                 | Width                       | 50 mm  |
| Height                               | 273 mm                 | Material                    | stainless steel  |
| Outreach                             | 202 mm                 | Note                        | corresponds to the German and European drinking water regulation/directive |
| Outlet                               | with swivelling outlet | Cartridge size              | 35 mm  |
| Discharge height                     | 187 mm                 | Max. Flow rate at 3 bar     | 13,7 l/min   |
| Operating mode                       | Lever                  | Flow rate at 3 bar (cold)   | 10,9 l/min   |
| Drilling diameter                    | 35 mm                  | Flow rate at 3 bar (hot)    | 10,87 l/min  |
| Handle position                      | top                    | Flow rate at 3 bar (mix)    | 12,18 l/min  |
| Lever length                         | 119 mm                 | Size laminar flow regulator | M18,5x1  |
| Cartridge with ceramic sealing discs | Yes                    | Connection hoses            | 700 mm   |

