




# Lupo LED

Product number: 7062295
Configuration: L 900 mm, 15 W, black matt

## Configuration options

7062253 | L 450 mm, 8 W, aluminium coloured
7062254 | L 600 mm, 10 W, aluminium coloured
7062255 | L 900 mm, 15 W, aluminium coloured
7062256 | L 1200 mm, 18 W, aluminium coloured
7062293 | L 450 mm, 8 W, black matt
7062294 | L 600 mm, 10 W, black matt
7062295 | L 900 mm, 15 W, black matt
7062296 | L 1200 mm, 18 W, black matt

✓ linear light
✓ Under-cabinet/niche light
✓ 3900 K neutral white

Lamp mounted from below. Aluminium body with plastic cover, head to head installation possible.

**Individual lamp with switch**
— 230 V **(high voltage), 3900 K** neutral white
— 75 lumen/watt
— 14 x 40 mm (H x W)
— 80 mm connection line
— cable outlet rear left side of lamp
— when connecting several lights (e.g. with end-to-end mounting or using a connecting cable), the existing “back-to-back” connectors allow each light to be switched on and off independently of the others
— **max. 200 watts can be connected**
— **mains connection HV (7062249 white or 7062269 black) to be ordered separately**
**This product contains a light source of energy efficiency class G.**

more infos...

## Technical data

| | |
|---|---|
| Article type | Luminaire |
| Height | 14 mm |
| Width | 900 mm |
| Energy efficiency class | G |
| Mains voltage | 230 V |
| Transformer / converter required | No. Mains cable HV must be ordered separately. |
| Mounting/Fixing | Base unit installation (wall unit/ shelf) |
| Note | max. 10 lamps can be connected |
| Material housing | aluminium |
| Certification | CE |
| Switch | Yes |

| | |
|---|---|
| Shape | angular |
| Length of the supply line (primary) | 80 mm |
| Illuminant included | Yes |
| Colour temperature | 3900 K neutral white |
| Illuminant type | LED |
| Replaceable illuminant | No |
| Light yield | 75 lumen/watt |
| Connection | One-sided |
| Material cover | plastic |
| Design | linear light<br>Under-cabinet/niche light |
| Illuminant power | 15 watts |