





Kludi E-GO-L Sensor

Product number: 5023129

Configuration: black matt, with plug, high pressure

Configuration options

5023128 | chrome, with plug, high pressure 5023129 | black matt, with plug, high pressure

- √ Sink faucet
- √ high pressure
- ✓ Swivelling

Single lever faucet. With swivelling outlet, laminar aerator and ceramic cartridge with hot-water limiter. Incl. built-in sensor for contactless operation and dirt strainer.

- can be operated either by sensor or manually
- water flow and temperature can be set as required
- water flow is activated by hand movement
- integrated cleaning mode for problem-free cleaning of the faucet
- adjustable sensor time for environmentally friendly and economical water consumption
- thanks to the controllable run-on time, not a drop is wasted
- swivel range 360°
- drill Ø 35 mm
- including DO-IT connection hoses





more infos...



Technical data

Article type	Sink faucet
Brand	Kludi
Number of handles	1
Total installation height	340 mm
Outreach	195 mm
Outlet	Swivelling
Discharge height	315 mm
Operating mode	Sensor Lever
Drilling diameter	35 mm
Handle position	right
Lever length	95 mm
Manufacturer's warranty	5 years manufacturer's warranty (except on wearing parts) 10-year after-sales guarantee on spare parts
Cartridge with ceramic sealing discs	Yes
Swivel range outlet	360°
Beam type	Laminar beam
Factory customer service	Yes

Type of fitting	Single lever faucet
Operating pressure	high pressure
Width	210 mm
Mounting/Fixing	surface mounting
Hose thread	3/8"
Worktop thickness	60 mm
Swivel range handle	43 °
Number of tap holes	1
ECO function	Flow limiter Controllable overrun time Water saving function
ECO function Temperature limiter/scald protection	Controllable overrun time
200 (4.1040)	Controllable overrun time Water saving function
Temperature limiter/scald protection	Controllable overrun time Water saving function Yes
Temperature limiter/scald protection Minimum distance wall to centre tap hole	Controllable overrun time Water saving function Yes 43 mm
Temperature limiter/scald protection Minimum distance wall to centre tap hole Anti-limestone jet regulator	Controllable overrun time Water saving function Yes 43 mm Yes