




Lista 30 LED

Product number: 7062068

Configuration: L 1200 mm, 11 W, stainless steel coloured

Configuration options

- 7062065 | L 450 mm, 3.8 W, stainless steel coloured
- 7062066 | L 600 mm, 5.3 W, stainless steel
- 7062067 | L 900 mm, 8.2 W, stainless steel coloured
- 7062068 | L 1200 mm, 11 W, stainless steel coloured
- 7062195 | L 450 mm, 3.8 W, black matt
- 7062196 | L 600 mm, 5.3 W, black matt
- 7062197 | L 900 mm, 8.2 W, black
- 7062198 | L 1200 mm, 11 W, black matt

- ✓ lit glass pane
- ✓ 4200 K neutral white
- ✓ angular

Lit glass shelf. Aluminium body, **stainless steel coloured** or **black matt**, mat safety glass, with LED lighting, uniform illumination over the entire width upward and downward, free-hanging attachment up to a shelf depth of 200 mm, screws mounted invisibly on the back.

Lit glass shelf with switch

- 4200 K neutral white
- 83 lumen/watt
- switch integrated into the bottom of the glass shelf
- **converter integrated into lit glass shelf**
- 2000 mm mains connection line, flat Euro plug enclosed separately
- cable outlet rear right of lamp
- bearing capacity approx. 10 kg

This product contains a light source of energy efficiency class G.



[more infos...](#)

Technical data

Article type	lit glass pane	Illuminant included	Yes
Height	33,5 mm	Housing colour	stainless-steel coloured
Width	1.200 mm	Colour temperature	4200 K neutral white
Energy efficiency class	G	Illuminant type	LED
Transformer / converter required	Yes, included and integrable	Replaceable illuminant	No
Plug type	Flat plug	Light yield	83 lumen/watt
Mounting/Fixing	Screw fastening screwable Wall mounting	Connection	One-sided
Material housing	aluminium	Material cover	safety glass
Switch	Yes	Cover colour	glass (LSG matt)
Shape	angular	Homogeneous light field without visible LED points	Yes
Length of the supply line (primary)	2.000 mm	Design	lit glass pane
Carrying capacity	ca. 10 kg	Illuminant power	11 watts