



## LINEA Aqvella system

Product number: 5021345

Configuration: black matt, high pressure

### Configuration options

5021344 | stainless steel coloured, high pressure

5021345 | black matt, high pressure

- ✓ Sink faucet
- ✓ high pressure
- ✓ energy-saving cold start function

Sparkling water single lever mixer faucet including cooling and filter system. With swivelling outlet, side lever, laminar jet regulator and ceramic cartridge.

— set consisting of faucet and technical unit (matt black) with cooling system, filter, filter head and standard CO2 cartridge. (425 g)

— technical unit: 455 x 210 x 425 mm (H x W x D)

— separate turning handle on the left for sparkling (classic + medium), chilled and filtered (still) water, control lever on the right for tap water

— integrated LED ring shows the different water modes with different colours.

— water temperature flexibly adjustable between 4 and 12°C

— energy-saving technology unit with low power consumption

— swivel range 360°

— drill Ø 35 mm

— corresponds to the German and European drinking water regulation/directive



[more infos...](#)

## Technical data

Article type	Sink faucet	Factory customer service	No
Brand	LINEA	Type of fitting	Single lever faucet
Number of handles	2	Operating pressure	high pressure
Total installation height	340 mm	Width	52 mm
Outreach	240 mm	Further	incl. cooling and filter system Technical unit: 455 x 210 x 425 mm (H x W x D) separate rotary handle on the left for carbonated (Classic + Medium), chilled and filtered (Still) water Control lever right for tap water integrated LED ring indicates the different water modes through different colors
Discharge height	290 mm	Temperature setting	Water temperature adjustable between 4 - 12 °C
Operating mode	Lever	Consisting of	Set consisting of fitting and technical unit (black matt) with cooling system, filter, filter head, and standard Co2 cartridge (425 g)
Drilling diameter	35 mm	Number of tap holes	1
Handle position	left and right	Hoses preassembled	Yes
Manufacturer's warranty	5 years manufacturer's warranty (except on wearing parts) 10-year after-sales guarantee on spare parts Your claim to customer service during the warranty period will be settled individually by agreement.	Cartridge size	35 mm
Cartridge with ceramic sealing discs	Yes	ECO function	energy-saving cold start function
Swivel range outlet	360°	Minimum distance wall to centre tap hole	0 mm
Beam type	Laminar beam	Connection hoses	600 mm