

## PRIME flow P-E-Jal Col 150 wall conduct incl. THERMOBOX square

Product number: 4050014

Configuration: black matt

### Configuration options

4050014 | black matt

- ✓ Wall sleeve
- ✓ N-click system with integrated latching elements
- ✓ Wall mounting

Wall conduct, incl. THERMOBOX heat retention system and P-E-Jal Col stainless steel external blind for installation close to the ground and for conventional installation at ceiling height.

Two-stage installation:

1. Assembly of the separately packaged construction kit
  2. Toolless insertion of the heat retention system and the blind — N-Klick system for secure connection with the universal connector
- direct connection of the flat adapter, round pipe or round pipe bends
  - Blower-Door certified (necessary opening pressure >65 Pa) Raw construction set:
  - raw construction set for installation in the wall at any time
  - max. wall thickness 550 mm, can be shortened to 220 mm
  - core hole drilling in nominal Ø 162 mm
  - polystyrene plugs to protect against dirt during the construction phase
  - wall sleeve for tool-free installation and sealing against leakage

[more infos...](#)

### Technical data

Article type	Wall sleeve	Shape	angular
Brand	PRIME flow	Suitable wall thickness	max. wall thickness 550 mm
Material	stainless steel/plastic	Wall box version	wall conduct, incl. THERMOBOX heat retention system and P-E-Jal Col stainless steel external blind for installation close to the ground and for conventional installation at ceiling height
Properties	can be shortened	System dimension	150
Mounting/Fixing	N-click system with integrated latching elements Wall mounting	Ventilation system	COMPAIR PRIME flow®
Certification	Blower-Door certified (required opening pressure >65 Pa)	Opening pressure	> 65 Pa
Suitable for	direct connection of the flat adapter, round pipe or round pipe bends	Rohbauset	raw construction set for installation in the wall at any time max. wall thickness 550 mm, can be shortened to 220 mm core hole drilling in nominal Ø 162 mm polystyrene plugs to protect against dirt during the construction phase wall sleeve for tool-free installation and sealing against leakage
Shortenability	can be shortened to 220 mm		