



## Nose colour change LED

Product number: 7061130

Configuration: subsequent lamp without switch, LIC LED system compatible, stainl. steel coloured

## **Configuration options**

7061130 | subsequent lamp without switch, LIC LED system compatible, stainl. steel coloured

- $\checkmark$  Surface-mounted lamp
- √ Built-in lamp
- √ 2700 K warm white to 6500 K cold white

Surface mounted lamp for kitchen islands. Aluminium body, 180° rotatable, not suitable for mounting above a hob.

- 9.5 watts, 12 V
- continuous control of the light colour from 2700 K warm white to 6500 K cold white
- memory function: the last setting is stored
- dimmer function: brightness continuously dimmable
- 82 lumen/watt at 6500 K cold white
- 17 mm bore for plug-in connector, for plate thicknesses up to 60 mm
- 1500 supply line with mini plug-in system

This product contains a light source of energy efficiency class G.

More information about the LIC LED system







more infos...

## Technical data

Article type	Luminaire
Drilling diameter	17 mm
Width	344 mm
Energy efficiency class	G
Transformer / converter required	Yes, must be ordered separately
Mounting/Fixing	surface mounting
Note	not suitable for mounting above a hob
Material housing	aluminium
Switch	No
Shape	angular
Memory function	Yes
Length of the supply line (primary)	1.500 mm
Illuminant included	Yes
Dimmer	Yes
Suitable panel thickness	up to 60 mm

Housing colour	stainless-steel coloured
Colour temperature	2700 K warm white to 6500 K cold white
Colour temperature adjustable	stepless
Type of dimming	brightness continuously dimmable
LIC system compatible	Yes
Plug-in system	with mini plug-in system
Swivel range	180 °
Illuminant type	LED
Replaceable illuminant	No
Light yield	82 lumen/watt
Connection	One-sided
Design	Surface-mounted lamp Built-in lamp
Dimming function (composite)	Yes, brightness continuously dimmable
Illuminant power	9.5 watts



## Accessories

7061025	LED converter 12, grey
7061026	LED converter 30, grey
7061049	LED connection line, Connecting element, white, L 2000 mm
7061403	MEC Driver LED converter, 60/72 W, 12/24 V
7061426	MEC Driver LED 1-channel module radio/ZigBee, Accessory, 12 V
7061428	MEC Driver LED 4-channel module radio/ZigBee, Accessory, 12 V
7061431	MEC Driver LED remote control 1+4 channel ZigBee, white