



Easytrack pendant S

Product number: 7065150
Configuration: white matt

Configuration options
7065074 | black matt
7065150 | white matt

✓ Pendant light
✓ 2700 K warm white to 6000 K cold white
✓ 5 watts

Pendant light. Pendant S for Easytrack track. Powder-coated aluminium housing.
— 5 Watt, 48 VDC, IP20
— L 300 mm, Ø 30 mm
— infinitely variable adjustment of light colour from **2700 K** warm white to **6000 K** cool white
— max. 70 lumens/watt at **6000 K** cool white
— very high quality of light thanks to colour rendering index >90
— pendant length incl. luminaire continuously adjustable from 400 mm to 1600 mm
— with integrated ZigBee 3.0 control unit
— LIC 2.0/MEC LED system compatible
This product contains a light source of energy efficiency class F.

Tool-free click-in installation in the track. Held in place by magnet or additional mechanical lock!

more infos...

Technical data

Article type	Luminaire
Width	300 mm
Material	aluminium
Energy efficiency class	F
Mains voltage	48 VDC
Protection class	IP20
Smarthome	ZigBee 3.0
Mounting/Fixing	tool-free click-in installation in the track Held in place by a magnet or by additional mechanical locking!
Certification	CE
Surface/coating	powder coated
Illuminant included	Yes
Colour temperature	2700 K warm white to 6000 K cold white

Colour temperature adjustable	stepless
Type of dimming	brightness continuously dimmable
LIC system compatible	Yes
Illuminant type	LED
Colour rendering index	>90
Light yield	max. 70 lumen/watt at 6000 K cold white
Suspension	incl. light continuously adjustable from 400 mm to 1600 mm
Number of lamps	1
Segments infinitely adjustable	Yes
Design	Pendant light
Dimming function (composite)	brightness continuously dimmable
Illuminant power	5 watts