





Light profile colour change LED

Product number: 7061039
Configuration: single lamp, aluminium coloured

Configuration options
7061039 | single lamp, aluminium coloured

✓ ambient light
✓ Base light/niche light
✓ LED Stripe

Ambient light. Aluminium body, self-adhesive LED strip, can be shortened every 50 mm, can also be cut to mitre, no visible LED.

Individual lamp
— 7.8 watts per meter, 12 V
— continuous control of the light colour from **2700 K** warm white to **6500 K** cold white
— max. 80 lumen/watt at **6500 K** cold white
— light length 2600 mm
— 2000 mm two-sided supply line
— LED strip 2600 mm, two-sided feed-in
— LIC 2.0/MEC LED system compatible

This product contains a light source of energy efficiency class F.
The work top has to be lined on site with 16 mm wooden slats.

More information about the LIC/MEC LED system

CE M M F

more infos...

Technical data

Article type	Luminaire
Height	16 mm
Width	2.600 mm
Energy efficiency class	F
Transformer / converter required	Yes, must be ordered separately
Mounting/Fixing	self-adhesive surface mounting
Note	The work top has to be lined on site with 16 mm wooden slats.
Material housing	aluminium
Switch	No
Shortenability	may be shortened every 50 mm
Shape	straight
Length of the supply line (primary)	2.000 mm

Illuminant included	Yes
Housing colour	aluminium
Colour temperature	2700 K warm white to 6500 K cold white
Colour temperature adjustable	stepless
LIC system compatible	Yes
Illuminant type	LED
Replaceable illuminant	No
Light yield	80 lumen/watt at 6500 K cold white
Connection	On both sides
Homogeneous light field without visible LED points	Yes
Design	ambient light Base light/niche light LED Stripe
Power per metre	7.8 watts