



## Duplex E double USB A+C

Product number: 7054006

Configuration: square, with earthed plug socket, black matt

### Configuration options

- 7054002 | round, with earthed plug socket, stainless steel
- 7054004 | square, with earthed plug socket, stainless steel
- 7054006 | square, with earthed plug socket, black matt
- 7054007 | round, with earthed plug socket, black matt

- ✓ Built-in socket element
- ✓ 1 x earthed plug socket
- ✓ square

Socket element. Single and double USB A+C charger (charging station).  
Electric opening at the push of a button.

- 1 x USB charger type A, 5 VDC, IA/I out: 1 x 2100 mA
- 1 x USB charger type C, 5 VDC, IA/I out: 1 x 3000 mA
- 3680 watt/16 A, 250 VAC, IP20
- H05VV-F 3G 1.5 mm<sup>2</sup>
- 3-pole with earthing contact
- 2000 mm mains connection line with earthed plug
- drill Ø 105 mm
- installation depth approx. 48 mm
- increased contact protection
- space-saving cable routing (downwards or side cable outlet)
- simple and quick installation
- retrofitting possible
- integrated water drain



[more infos...](#)

## Technical data

|                                     |                                    |  |  |
|-------------------------------------|------------------------------------|--|--|
| Article type                        | Socket element                     | Mains plug loosely enclosed            | Yes  |
| Height                              | 118 mm                             | Colour bezel                           | black matt   |
| Drilling diameter                   | 105 mm                             | Colour socket                          | black  |
| Width                               | 118 mm                             | Cover/blind type                       | Electric   |
| Mains voltage                       | 250 VAC                            | Integrated water drain                 | Yes  |
| Protection class                    | IP20                               | Number of USB ports                    | 2  |
| Cable outlet                        | cable outlet on the side or bottom | USB type                               | USB-A<br>USB-C   |
| Max. connected load                 | 3680 watt                          | Total charging current                 | 3000 mA (USB-C)  |
| Mounting/Fixing                     | on the worktop installation        | Type of socket element                 | Built-in socket element  |
| Note                                | can be retrofitted                 | Switch type                            | Touch switch   |
| Further                             | 3-pole with earthing contact       | Conductor cross-section                | 1,5 mm <sup>2</sup>  |
| Certification                       | CE<br>TÜV                          | Rated current                          | 16 A   |
| Surface/coating                     | matt                               | Wiring                                 | 3-wire with free ends bared  |
| Shape                               | square                             | Number of sockets (total)              | 1  |
| Length of the supply line (primary) | 2.000 mm                           | Opening mechanism                      | Push-to-open   |
| Installation depth                  | 48 mm                              | Touch protection ("child safety lock") | with increased contact protection  |
| Version sockets                     | 1 x earthed plug socket            | USB version                            | 1 x USB charger type A, 5 VDC, IA/<br>I out: 2100 mA<br>1 x USB charger type C, 5 VDC, IA/<br>I out: 1 x 3000 mA |