



Vetro LED

Product number: 7064200

Configuration: single lamp without switch, white

Configuration options

7064200 | single lamp without switch, white

7064201 | single lamp w. LED Touch s. d., white

7064202 | set 2, white

7064203 | set 3, white

7064205 | set 5, white

7064210 | single lamp without switch, black

7064211 | single lamp w. LED Touch s. d., black

✓ Under-cabinet/niche light

✓ 4000 K neutral white

✓ 4 watts

Lamp mounted from below. Aluminium body with glass cover, frame stainless steel coloured, brushed, illumination without visible LED points.

Individual lamp without switch or with LED Touch switch and dimmer (w. LED Touch s. d.)

— 4 watts, 12 V, 4000 K neutral white

— 90 lumen/watt

— dimmer function: brightness continuously dimmable

— 200 mm supply line, 2000 mm connection line with mini-plug-in system

— additional memory function: the last setting is stored for individual lamp with LED Touch switch and dimmer (7064201/7064211)

— not suitable for switchable sockets

Set 2, 3, 5 with LED Touch switch and dimmer consisting of:

— 1, 2 or 4 individual lamps without switch (7064200/7064210)

— 1 individual lamp with LED Touch switch and dimmer (7064201/7064211)

— 1 LED converter 1 (7064208)

— may be extended to 5 lamps

This product contains a light source of energy efficiency class F.



[more infos...](#)

Technical data

Article type	Luminaire	Housing colour	stainless steel-coloured brushed
Width	200 mm	Colour temperature	4000 K neutral white
Energy efficiency class	F	Type of dimming	brightness continuously dimmable
Transformer / converter required	Yes, must be ordered separately	Plug-in system	with mini plug-in system
Mounting/Fixing	Base unit installation (wall unit/shelf)	Illuminant type	LED
Material housing	aluminium	Replaceable illuminant	No
Length of connection cable (secondary)	2.000 mm	Light yield	90 lumen/watt
Certification	CE	Material cover	glass
Switch	No	Cover colour	white
Surface/coating	brushed	Homogeneous light field without visible LED points	Yes
Shape	angular	Design	Under-cabinet/niche light
Length of the supply line (primary)	200 mm	Dimming function (composite)	Yes, brightness continuously dimmable
Illuminant included	Yes	Illuminant power	4 watts
Dimmer	Yes		

Accessories

7061049	LED connection line, Connecting element, white, L 2000 mm
---------	---