


## Anelli LED black matt

Product number: 7061329

Configuration: set 3, 4000 K neutral white

### Configuration options

- 7061325 | single lamp without switch, 4000 K neutral white
- 7061327 | set 2, 4000 K neutral white
- 7061329 | set 3, 4000 K neutral white
- 7061331 | set 5, 4000 K neutral white
- 7063359 | single lamp without switch, 3000 K warm white
- 7063361 | set 2, 3000 K warm white
- 7063363 | set 3, 3000 K warm white
- 7063365 | set 5, 3000 K warm white



- ✓ Built-in lamp
- ✓ Surface-mounted lamp
- ✓ 4000 K neutral white

Built-in lamp. Aluminium body, illumination without visible LED points.

Individual lamp without switch

- 4 watts, 12 V, two colour areas: 4000 K neutral white, 3000 K warm white
- 62 lumen/watt
- 2000 mm supply line
- drill  $\varnothing$  58 mm

Set 2, 3, 5 without switch consisting of:

- 2, 3 or 5 individual lamps without switch (7061325/7063359)
- 1 LED converter 20 (7062309)
- may be extended to 5 lamps

This product contains a light source of energy efficiency class F.



[more infos...](#)

### Technical data

|                                     |   |  |                                       |
|-------------------------------------|---|--|---------------------------------------|
| Article type                        | Luminaire   | Outer diameter                                     | 64,8 mm                               |
| Drilling diameter                   | 58 mm   | Illuminant included                                | Yes                                   |
| Width                               | 64,8 mm   | Housing colour                                     | black matt                            |
| Energy efficiency class             | F   | Colour temperature                                 | 4000 K neutral white                  |
| Transformer / converter required    | Yes, included   | Illuminant type                                    | LED                                   |
| Protection class                    | III   | Replaceable illuminant                             | No                                    |
| Mounting/Fixing                     | Base unit installation (wall unit/shelf) installation | Light yield  | 62 lumen/watt                         |
| Material housing                    | aluminium   | Connection   | One-sided                             |
| Switch                              | No  | Homogeneous light field without visible LED points | Yes                                   |
| Surface/coating                     | matt  | Design   | Built-in lamp<br>Surface-mounted lamp |
| Shape                               | round   | Illuminant power                                   | 4 watts                               |
| Length of the supply line (primary) | 2.000 mm  |  |                                       |

**Accessories**

|         |  |
|---------|--|
| 7061049 | LED connection line, Connecting element, white, L 2000 mm      |
| 7061323 | Anelli mounting ring, Accessory, matt black, 15 mm             |
| 7062309 | LED converter 20, grey   |
| 7051089 | Radio remote control, aluminium coloured                       |
| 7062094 | Slash switch, Switch, stainless steel                          |
| 7053098 | Rondo surface mounted switch, Switch, stainless steel coloured |
| 7053096 | Rondo surface mounted switch, Switch, white                    |
| 7031092 | Mains connection line with valance switch, Switch, white       |