

Light profile LED

Product number: 7061044

Configuration: individual lamp, aluminium coloured

Configuration options

7061044 | individual lamp, aluminium coloured

- ✓ ambient light
- ✓ LED Stripe
- ✓ Base light/niche light


Ambient light. Made of aluminium body, self-adhesive LED strip, may be shortened every 50 mm, can also be cut to mitre, no visible LED.

Individual lamp

- 12.96 watts = 4.8 watt pro metre, 12 V
- 4000 K neutral white
- 79 lumen/watt
- light length 2600 mm
- 2000 mm two-sided supply line
- LED strip 2600 mm, two-sided feed-in

This product contains a light source of energy efficiency class F.

The work top has to be lined on site with 16 mm wooden slats.



[more infos...](#)

Technical data

Article type	Luminaire	Length of the supply line (primary)	2.000 mm
Width	2.600 mm	Illuminant included	Yes
Energy efficiency class	F	Housing colour	aluminium
Transformer / converter required	Yes, must be ordered separately	Colour temperature	4000 K neutral white
Protection class	III	Illuminant type	LED
Mounting/Fixing	self-adhesive surface mounting	Replaceable illuminant	No
Note	The work top has to be lined on site with 16 mm wooden slats.	Light yield	45 lumen/watt
Material housing	aluminium	Connection	On both sides
Certification	CE F-sign MM sign	Homogeneous light field without visible LED points	Yes
Switch	No	Design	ambient light LED Stripe Base light/niche light
Shortenability	may be shortened every 50 mm	Power per metre	4.8 watts
Shape	straight		

Accessories

7061049	LED connection line, Connecting element, white, L 2000 mm
7061302	Light profile LED strip neutral white, Accessory, L 2600 mm, 13 W/12 V
7061026	LED converter 30, grey