



## PRIME flow P-E-Jal Col flow 150 wall conduct incl. THERMOBOX

Product number: 4051067

Configuration: white, stainless steel

### Configuration options

4051067 | white, stainless steel

- ✓ Wall sleeve
- ✓ installation in the wall
- ✓ N-click system with integrated latching elements

Wall conduct, incl. THERMOBOX heat retention system and **P-E-Jal Col stainless steel external blind** for installation close to the ground and for conventional installation at ceiling height.

Two-stage installation:

1. Assembly of the separately packaged construction kit
2. Toolless insertion of the heat retention system and the blind

- N-Klick system for secure connection with the universal connector
- direct connection of the flat adapter, round pipe or round pipe bends
- Blower-Door certified (necessary opening pressure >65 Pa)

Raw construction set:

- raw construction set for installation in the wall at any time
- max. wall thickness 550 mm, can be shortened to 220 mm
- core hole drilling in nominal  $\varnothing$  162 mm
- polystyrene plugs to protect against dirt during the construction phase
- wall sleeve for tool-free installation and sealing against leakage



[more infos...](#)

### Technical data

|                 |   |                         |   |
|-----------------|---|-------------------------|---|
| Article type    | Wall sleeve   | Outer diameter          | 150 mm  |
| Brand           | PRIME flow  | Suitable wall thickness | max. wall thickness 550 mm  |
| Material        | stainless steel/plastic   | Wall box version        | wall conduct, incl. THERMOBOX heat retention system and P-E-Jal Col stainless steel external blind for installation close to the ground and for conventional installation at ceiling height |
| Properties      | can be shortened  | System dimension        | 150   |
| Mounting/Fixing | installation in the wall<br>N-click system with integrated latching elements  | Output drive            | angular   |
| Suitable for    | direct connection of the flat adapter, round pipe or round pipe bends   | Ventilation system      | COMPAIR PRIME flow <sup>®</sup>   |
| Shortenability  | can be shortened to 220 mm  | Opening pressure        | > 65 Pa   |
| Consisting of   | polystyrene plugs to protect against dirt during the construction phase<br>wall sleeve for tool-free installation and sealing against leakage |                         |   |

