



Easytrack linear Light

Product number: 7065149
Configuration: L 460 mm, 18.1 W, white matt

Configuration options
7065072 | L 233 mm, 9.1 W, black matt
7065073 | L 460 mm, 18.1 W, black matt
7065148 | L 233 mm, 9.1 W, white matt
7065149 | L 460 mm, 18.1 W, white matt

✓ 2700 K warm white to 6000 K cold white
✓ 18.1 watts

Linear light for Easytrack busbar. Powder-coated aluminium housing.
— 48 VDC, IP20
— stepless control of the light colour from **2700 K** warm white to **6000 K** cold white
— max. 144 lumen/watt at **6000 K** cold white
— very high light quality thanks to colour rendering index >90
— strong glare-free light (optical lenses) in modern raster optics
— Ideal for illuminating work surfaces (e.g. cooking island)
— with integrated ZigBee 3.0 controller
— LIC 2.0/MEC LED system compatible

This product contains a light source with the energy efficiency class D.

Tool-free click-in installation in the track. Held in place by a magnet or by additional mechanical locking!

more infos...

Technical data

Article type	Luminaire
Height	42,5 mm
Width	460 mm
Material	aluminium
Energy efficiency class	D
Mains voltage	48 VDC
Protection class	IP20
Mounting/Fixing	tool-free click-in installation in the track held in place by a mechanical locking

Further	strong glare-free light (optical lenses) in modern louvre optics
Certification	CE
Surface/coating	powder coated
Intended use	ideal for illuminating work surfaces (e.g. cooking island)
Colour temperature	2700 K warm white to 6000 K cold white
Illuminant type	LED
Light yield	max. 144 lumen/watt at 6000 K cold white
Illuminant power	18.1 watts