



flow Star GTS 150 wall conduct

Product number: 4043040
Configuration: white, stainless steel

Configuration options
4043040 | white, stainless steel

✓ Wall sleeve
✓ installation in the wall

With connection to round pipe Ø 150 mm and round **external stainless-steel cover.**
— required opening pressure 150 Pa
— stainless steel cover Ø 220 mm
— hose/pipe connector Ø 150 mm, connector depth 24 mm
— installation depth 314–550 mm, can be shortened to 250 mm, wall penetration Ø about 155 mm
— for the installation of the mounting pipe, a core drilling hole (Ø 155 mm) is recommended

more infos...

Technical data

Article type	Wall sleeve
Height	220 mm
Width	220 mm
Material	stainless steel
Properties	can be shortened rust-free
Mounting/Fixing	installation in the wall
Certification	stainless
Diameter	stainless steel cover Ø 220 mm
Shortenability	can be shortened to 250 mm
Shape	round

Outer diameter	150 mm
Support depth	24 mm
Diameter wall opening	155 mm
Installation depth	314–550 mm
Wall box version	with connection to round pipe Ø 150 mm and round external stainless-steel cover
Pipe socket dimension	hose/pipe connector Ø 150 mm
System dimension	150
Output drive	round
Ventilation system	COMPAIR flow 150
Opening pressure	150 Pa

Dimensional sketch (PDF)

