




# Profile light Neva LED

Product number: 7062513
Configuration: L 1500 mm, 24 W

**Configuration options**
7062510 | L 600 mm, 9.6 W
7062511 | L 900 mm, 14.4 W
7062512 | L 1200 mm, 19.2 W
7062513 | L 1500 mm, 24 W

✓ linear light
✓ Under-cabinet/niche light
✓ 3000 K warm white, 4000 K neutral white, 5000 K cold white

Lamp for mounting from below. Plastic housing with overlapping end caps. Can be shortened every 50 mm. Illumination without visible LED points with integrated switch.

**Individual lamp with switch**

— 16 watts per meter, 24 V, three colour ranges: **3000 K** warm white, **4000 K** neutral white, **5000 K** cold white
— 75 lumen/watt
— very high quality of light thanks to colour rendering index >90
— sliding switch on each light for adjustable light colour: warm white/neutral white/ cool white
— memory function: the last setting is stored
— dimming function: brightness can be continuously dimmed
— 2000 mm supply line with mini-plug-in system
— incl. fastening clips
**— incl. 30 watt converter**

**This product contains a light source with the energy efficiency class E.**

CE

more infos...

Naber GmbH
Enschedestr. 24
DE-48529 Nordhorn

Tel. +49 5921 704-0
Fax +49 5921 704-140
naber@naber.com

## Technical data

| | |
|---|---|
| Article type | Luminaire |
| Height | 12,4 mm |
| Width | 1.500 mm |
| Material | aluminium |
| Energy efficiency class | E |
| Mains voltage | 12 VDC |
| Transformer / converter required | Yes, included |
| Protection class | IP20 |
| Protection class | III |
| Mounting/Fixing | Base unit installation (wall unit/ shelf) |
| Further | sliding switch on each light for adjustable light colour: warm white/ neutral white/ cool white |
| Certification | CE |
| Switch | Yes |
| Shortenability | may be shortened every 50 mm |
| Shape | angular |
| Memory function | Yes |

| | |
|---|---|
| Length of the supply line (primary) | 2.000 mm |
| More parts | incl. mounting clips |
| Dimmer | Yes |
| Colour temperature | 3000 K warm white, 4000 K neutral white, 5000 K cold white |
| Type of dimming | brightness continuously dimmable |
| Illuminant type | LED |
| Colour rendering index | >90 |
| Light yield | 75 lumen/watt |
| Material cover | plastic |
| Homogeneous light field without visible LED points | Yes |
| Radiation angle | 113° |
| Design | linear light<br>Under-cabinet/niche light |
| Dimming function (composite) | Yes, brightness continuously dimmable |
| Power per metre | 16 watts |
| Illuminant power | 24 watts |

## Dimensional sketch (PDF)

