



AstraLED SE aluminium coloured

Product number: 7063343

Configuration: individual lamp without switch, 3900 K neutral white

Configuration options

- 7063314 | individual lamp without switch, 3000 K warm white
- 7063315 | single lamp w. LED Touch s. d., 3000 K warm white
- 7063316 | set-2, 3000 K warm white
- 7063317 | set-3, 3000 K warm white
- 7063319 | set-5, 3000 K warm white
- 7063343 | individual lamp without switch, 3900 K neutral white
- 7063344 | single lamp w. LED Touch s. d., 3900 K neutral white
- 7063345 | set-2, 3900 K neutral white
- 7063346 | set-3, 3900 K neutral white
- 7063347 | set-5, 3900 K neutral white

- ✓ Under-cabinet/niche light
- ✓ 3900 K neutral white
- ✓ 5 watts

Lamp for mounting from below. Aluminium housing, 5 mm, illumination without visible LED points with integrated touch switch.

Individual lamp without or with LED Touch switch and dimmer (w. LED Touch s. d.)

- 5 watt, 24 V, two colour ranges: **3000 K** warm white, **3900 K** neutral white
- 65 lumen/watt
- brightness continuously dimmable using LED touch switch and dimmer
- 200 mm supply line, 2000 mm connecting line with mini-plug-in system
- additional memory function: the last setting is saved

Set 2, 3, 5 with LED Touch switch and dimmer consisting of:

- 1, 2 or 4 individual lamps with switch (7063314/7063343)
- 1 individual lamp with LED Touch switch and dimmer (7063315/7063344)
- 1 LED converter 2430 (7062250)
- may be extended to 6 lamps

This product contains a light source with the energy efficiency class F.



[more infos...](#)

Technical data

| | | | |
|---|--|---|--|
| Article type | Luminaire | Dimmer | Yes |
| Height | 5 mm | Housing colour | aluminium coloured |
| Width | 190 mm | Colour temperature | 3900 K neutral white |
| Energy efficiency class | F | Type of dimming | brightness continuously dimmable |
| Transformer / converter required | Yes, must be ordered separately | Plug-in system | with mini plug-in system |
| Protection class | III | Illuminant type | LED |
| Mounting/Fixing | Base unit installation (wall unit/ shelf) | Replaceable illuminant | No |
| Material housing | aluminium | Light yield | 65 lumen/watt |
| Length of connection cable (secondary) | 2.000 mm | Homogeneous light field without visible LED points | Yes |
| Switch | No | Touch function | Yes |
| Shape | angular | Design | Under-cabinet/niche light |
| Memory function | Yes | Dimming function (composite) | Yes, brightness continuously dimmable |
| Length of the supply line (primary) | 150 mm | Illuminant power | 5 watts |
| Illuminant included | Yes | | |