




Ø 105 Ø 115



Twist double plug socket

Product number: 7053021

Configuration: with earthed plug sockets, stainless steel coloured

Configuration options

7053021 | with earthed plug sockets, stainless steel coloured

7053025 | with Belgian/French sockets, stainless steel coloured

7053059 | with Swiss sockets, stainless steel coloured

7053075 | with earthed plug sockets, black matt

7053076 | with earthed plug sockets, white matt

7053085 | with Belgian/French sockets, black matt

7053086 | with Belgian/French sockets, white matt

7053189 | with Swiss sockets, black matt

- √ Built-in socket element
- √ 2 x earthed plug socket
- ✓ round

Socket element. 2-fold.

- 3680 watt/16 A, 250 VAC, IP20
- H05VV-F 3G1
- 3-pin with earthing contact
- 2000 mm mains connection line, earthing contact plug enclosed loosely
- drill Ø 105 mm, for board thicknesses from 8 mm
- increased contact protection
- cable outlet below side



more infos...



Technical data

Article type	Socket element	Version sockets	2 x earthed plug socket
Drilling diameter	105 mm	Mains plug loosely enclosed	Yes
Width	180 mm	Colour bezel	stainless-steel coloured
Mains voltage	250 VAC	Colour socket	black
Protection class	IP20	Installation diameter	115 mm
Cable outlet	cable outlet rear side	Cover/blind type	Turning lid
Max. connected load	3680 watt	Integrated water drain	Yes
Mounting/Fixing	installation	Type of socket element	Built-in socket element
Further	on the worktop 3-pole with earthing contact	Wiring	3-wire with free ends bared
Certification	CE	Number of sockets (total)	2
Shape	round	Opening mechanism	Push-to-open
Length of the supply line (primary)	2.000 mm	Touch protection ("child safety lock")	with increased contact protection
Installation depth	40 mm	Worktop thickness	8 mm

Accessories

7053024 Hole saw, Ø 105 mm, for Twist and Duplex

Recommendations

7053024 Hole saw, Ø 105 mm, for Twist and Duplex