

Lupo LED

Product number: 7062253

Configuration: L 450 mm, 8 W, aluminium coloured

Configuration options

7062253 | L 450 mm, 8 W, aluminium coloured
 7062254 | L 600 mm, 10 W, aluminium coloured
 7062255 | L 900 mm, 15 W, aluminium coloured
 7062256 | L 1200 mm, 18 W, aluminium coloured
 7062293 | L 450 mm, 8 W, black matt
 7062294 | L 600 mm, 10 W, black matt
 7062295 | L 900 mm, 15 W, black matt
 7062296 | L 1200 mm, 18 W, black matt



- ✓ linear light
- ✓ Under-cabinet/niche light
- ✓ 3900 K neutral white

Lamp mounted from below. Aluminium body with plastic cover, head to head installation possible.

Individual lamp with switch

- 230 V (**high voltage**), 3900 K neutral white
- 75 lumen/watt
- 14 x 40 mm (H x W)
- 80 mm connection line
- cable outlet rear left side of lamp
- when connecting several lights (e.g. with end-to-end mounting or using a connecting cable), the existing “back-to-back” connectors allow each light to be switched on and off independently of the others
- **max. 200 watts can be connected**
- mains connection HV (7062249 white or 7062269 black) to be ordered separately

This product contains a light source of energy efficiency class G.



[more infos...](#)

Technical data

Article type	Luminaire	Shape	angular
Height	14 mm	Length of the supply line (primary)	80 mm
Width	450 mm	Illuminant included	Yes
Energy efficiency class	G	Colour temperature	3900 K neutral white
Mains voltage	230 V	Illuminant type	LED
Transformer / converter required	No. Mains cable HV must be ordered separately.	Replaceable illuminant	No
Mounting/Fixing	Base unit installation (wall unit/shelf)	Light yield	75 lumen/watt
Note	max. 10 lamps can be connected	Connection	One-sided
Material housing	aluminium	Material cover	plastic
Certification	CE	Design	linear light Under-cabinet/niche light
Switch	Yes	Illuminant power	8 watts