



## Stretto colour change LED

Product number: 7062206

Configuration: single lamp without switch, stainless steel col.

### Configuration options

7062206 | single lamp without switch, stainless steel col.

- ✓ Under-cabinet/niche light
- ✓ 2700 K warm white to 6500 K cold white
- ✓ 3 watts

Lamp mounted from below. Aluminium body, translucent light diffuser, illumination without visible LED points with colour change.

Individual lamp without switch

- 3 watts, 12 V
- continuous control of the light colour from 2700 K warm white to 6500 K cold white
- memory function: the last setting is stored
- dimmer function: brightness continuously dimmable
- max. 78 lumen/watt at 6500 K cold white
- 1800 mm supply line with mini-plug-in system
- LIC LED system compatible

This product contains a light source of energy efficiency class G.

More information about the LIC LED system



[more infos...](#)

### Technical data

|                                     |                                          |                                                    |                                         |
|-------------------------------------|------------------------------------------|----------------------------------------------------|-----------------------------------------|
| Article type                        | Luminaire                                | Colour temperature                                 | 2700 K warm white to 6500 K cold white  |
| Width                               | 200 mm                                   | Colour temperature adjustable                      | stepless                                |
| Energy efficiency class             | G                                        | Type of dimming                                    | brightness continuously dimmable        |
| Transformer / converter required    | Yes, must be ordered separately          | LIC system compatible                              | Yes                                     |
| Mounting/Fixing                     | Base unit installation (wall unit/shelf) | Plug-in system                                     | with mini plug-in system                |
| Material housing                    | aluminium                                | Illuminant type                                    | LED                                     |
| Switch                              | No                                       | Replaceable illuminant                             | No                                      |
| Shape                               | angular                                  | Light yield                                        | max. 85 lumen/watt at 6500 K cold white |
| Memory function                     | Yes                                      | Cover colour                                       | transparent                             |
| Length of the supply line (primary) | 1.800 mm                                 | Homogeneous light field without visible LED points | Yes                                     |
| Illuminant included                 | Yes                                      | Design                                             | Under-cabinet/niche light               |
| Dimmer                              | Yes                                      | Dimming function (composite)                       | Yes, brightness continuously dimmable   |
| Housing colour                      | stainless-steel coloured                 | Illuminant power                                   | 3 watts                                 |

## Accessories

|         |                                                                              |
|---------|------------------------------------------------------------------------------|
| 7061049 | LED connection line, Connecting element, white, L 2000 mm                    |
| 7061286 | FW function converter, module 2 (radio), 15 W, 4-way distributor             |
| 7061271 | FW function converter, module 2 (radio), 30 W, 6-way distributor             |
| 7061273 | FW function converter, module 2 (radio), 60 W, 6-way distributor             |
| 7061287 | FW function converter, module 3 (Bluetooth + radio), 15 W, 4-way distributor |
| 7061281 | FW function converter, module 3 (Bluetooth + radio), 30 W, 6-way distributor |
| 7061283 | FW function converter, module 3 (Bluetooth + radio), 60 W, 6-way distributor |
| 7061285 | 1-channel colour change remote control, white                                |
| 7061284 | 230 volt connecting line, Connection line/element, L 300 mm, white           |
| 7061279 | 230 volt connecting line, Connection line/element, L 1000 mm, white          |
| 7061244 | Distributor 12 V, Distributor, black                                         |
| 7061403 | MEC Driver LED converter, 60/72 W, 12/24 V                                   |
| 7061426 | MEC Driver LED 1-channel module radio/ZigBee, Accessory, 12 V                |
| 7061428 | MEC Driver LED 4-channel module radio/ZigBee, Accessory, 12 V                |
| 7061431 | MEC Driver LED remote control 1+4 channel ZigBee, white                      |